

## Blue Jeans Relay requirements

### Listener Service host OS

- CPU: 1.5GHz
- RAM: 1GB
- Java 1.7 or later
- Operating systems:
  - Debian, Ubuntu
  - RedHat, Fedora, CentOS
  - Windows Server 2008 or later

### Supported endpoints

Relay has been certified to work with the following Endpoint models and versions. In addition, compatibility is likely with similar models and versions.

- Polycom
  - HDX 6000 HD
    - Tested firmware: 3.0.5-22695, 3.1.1.3-36019, 3.1.3.2-38311, 3.1.3-38278, 3.1.4-43132, 3.1.5-5568, 3.1.6-46064
  - RealPresence Group 500, RealPresence Group 700
    - Tested firmware: 4.0.1-80438, 4.0.2, 4.1.3.2-200003, 4.1.4-180060, 4.1.5-180072, 4.2.0-11309
- Cisco/Tandberg (excluding CTS)
  - C20, C40, EX60, EX90, SX10, SX20
    - Tested firmware: TC4.2.1, TC7.1.4.908e4a9, TC6.3.0, TC6.2.0 Beta1, TC5.0.0 Beta, TC5.0.1.275220, TC7.2.0.aea6651, TC5.1.5, TC6.0.0.876266, TC6.3.0, TC7.1.4.908e4a9
- LifeSize
  - Room 220, Express 220
    - Tested firmware: LS\_EX2\_4.8.0 (59), LS\_RM2\_4.12.0 (30)
  - Icon 600
    - Tested firmware: LS\_RM3\_1.3.2 (2), LS\_RM3\_2.0.5 (764)

### Supported calendar servers

- Google Calendar
- Microsoft Exchange
  - Exchange 2010, Exchange 2013